

ARTICLE

Navigating the Future of Wearable Devices with Flexible Electronics

Alexandre Gabriel, Claude Charles,* Louis Andre, and Charlotte Antoine

UMR CNRS 8163 – STL, Université de Lille F-59000 Lille, France

*Corresponding author: Claudechar65@univ-lille.fr

(Received: 19 February 2020; Revised: 03 May 2020; Accepted: 16 June 2020; Published: 04 July 2020)

Abstract

The future of wearable devices is being revolutionized by the advent of flexible electronics, which offer unparalleled advantages in terms of comfort, adaptability, and functionality. Flexible electronics, composed of bendable, stretchable, and lightweight materials, enable the development of next-generation wearables that conform seamlessly to the human body, providing enhanced user experiences and extended applications. These advanced materials and manufacturing techniques allow for the integration of sensors, circuits, and energy storage components into fabrics and flexible substrates, creating devices that can monitor health metrics, track physical activities, and even provide therapeutic interventions in real-time. The integration of flexible electronics in wearables opens new possibilities in healthcare, fitness, and personal well-being. For instance, flexible sensors can continuously monitor vital signs such as heart rate, blood pressure, and glucose levels, enabling proactive health management and timely medical interventions. In sports and fitness, these devices can provide detailed performance analytics, helping individuals optimize their training routines. Moreover, flexible electronics pave the way for innovative consumer electronics, such as foldable displays and smart clothing. Despite the promising potential, challenges remain in ensuring the durability, biocompatibility, and energy efficiency of flexible wearable devices. Ongoing research and development are focused on overcoming these obstacles, making flexible electronics a cornerstone of the future of wearable technology.

Keywords: 3d Printing; Biomedical Devices; Graphene; Internet of Things; Flexible Flat Cables; Solar Cells; Photovoltaics

Abbreviations: PDMS: Polydimethylsiloxane, PET: Polyethylene Terephthalate PENG: Piezoelectric nanogenerator, PVA: Polyvinyl Alcohol, TENG: Triboelectric nanogenerator

1. Introduction

The advent of flexible electronics has opened up new avenues for seamless integration of innovative devices with the human body, addressing longstanding challenges posed by rigid electronics like motion artifacts and mechanical mismatch with soft tissues. From enabling natural movement to facilitating unobtrusive biomonitoring, flexible electronics show immense potential in diverse fields spanning the Internet of Things, wearable computing, and biomedical devices Fig. 1 [1, 2].

These cutting-edge systems typically comprise a flexible substrate, an active layer – often based on high-performance inorganic nanomaterials like graphene – and an interface layer, fabricated through techniques like 3D printing, physical transfer, or solution processes. With their ability to conform to curved surfaces, flexible electronics are particularly promising for applications like tactile pressure mapping, skin temperature monitoring, ECG tracking, and real-time sweat analysis




Figure 1. Four kinds of primary ergonomics methods of SWEs.

via integrated microfluidic sensing platforms [3, 4, 5, 6].

1.1 Design Concept


The design concept behind flexible electronics revolves around creating systems that can seamlessly integrate with the human body, enabling natural movement and unobtrusive monitoring. These devices typically comprise three key components:

1. **Flexible Substrate:** This serves as the foundation, providing a bendable and stretchable platform. Common materials used include polymers like polyimide, polyethylene terephthalate (PET), and polydimethylsiloxane (PDMS).
2. **Active Layer:** This layer houses the functional components, such as sensors, transistors, or electrodes. High-performance inorganic nanomaterials like graphene, carbon nanotubes, and metal oxides are often employed for their exceptional electrical, thermal, and mechanical properties.
3. **Interface Layer:** This layer facilitates seamless interaction between the device and the human body, ensuring comfort and biocompatibility. It may incorporate soft, breathable materials like hydrogels or elastomers Fig. 2.

The design process involves careful consideration of the following factors:

- **Mechanical Flexibility:** Devices must be able to conform to curved surfaces and withstand repeated bending and stretching without compromising performance.
- **Biocompatibility:** Materials used should be non-toxic, non-allergenic, and minimally invasive to the body.
- **Lightweight and Thin:** Devices should be lightweight and ultra-thin to ensure comfort and minimize interference with daily activities.
- **Power Efficiency:** Low power consumption is crucial for extended operation and minimizing heat generation, which could cause discomfort or safety concerns.

To achieve these design goals, innovative techniques like serpentine interconnects, self-similar geometries, and stretchable electronics are employed, enabling the devices to accommodate significant deformations while maintaining functionality [7].



2. Fabrication Process

The assembly process for flexible wire batteries involves fabricating a metal current collector in a serpentine geometry, followed by sequential deposition of the battery components. Specifically:

1. The Zn electrode is electroplated on the current collector.
2. A polyvinyl alcohol (PVA)-based polymer electrolyte is used.
3. Cellophane is wrapped around to protect the Zn anode.

As for the Ag electrode, it is constructed by embedding silver nanoparticle ink into a conductive thread and cold rolling. A key design aspect of these batteries is their segmented construction in the active materials and the use of 'self-similar' serpentine interconnect structures. This enables reversible stretchability up to 300%, facilitating seamless integration with flexible and wearable electronics [8, 9].

2.1 Flexible Wire Batteries

Researchers have developed a new technology called 'flexible wire batteries' that can stretch and deform without losing power, making them ideal for powering flexible and wearable electronics.

These batteries use a hydrogel electrolyte that allows them to maintain functionality even when stretched up to 22%. Flexible wire batteries come in various chemistries, including:

- **Lithium-ion:** These batteries offer high energy density but use a flammable organic electrolyte.
- **Zinc-ion:** Safer than lithium-ion as they use an aqueous electrolyte, but with lower energy density.

The design of flexible wire batteries prioritizes thinness (less than 2mm in diameter) and lightweight (a few grams), enabling seamless integration into wearable devices and smart clothing without adding bulk or discomfort. Despite their flexibility, these batteries have demonstrated remarkable resilience, consistently powering devices like servo motors even after enduring significant abuse like stretching, twisting, and impact Fig. 3 [10]. As electronic devices continue to migrate closer to the




Figure 3. Physiological sensing systems.

human body, the demand for power sources that can flex and stretch with the skin is expected to surge in the next decade. Potential applications include:

- Fitness trackers
- Health monitors
- Smart textiles
- Medical patches

Ongoing research efforts aim to improve the energy density, charging capabilities, and manufacturing processes of flexible wire batteries [5]. Achieving an optimal balance between energy density, power density, and mechanical deformability remains a key challenge. Promising avenues include flexible solid polymer electrolytes, flexible current collectors, and origami-inspired flexible battery designs. Additionally, improving the flexibility, energy/power density, and cycle life of flexible lithium-ion batteries is a priority for future research [11].

3. Stretchable Serpentine Batteries

A key innovation in stretchable batteries is the serpentine ribbon current collector design. This configuration accommodates mechanical strain through out-of-plane rotations, reducing stress on the materials when stretched. The self-similar serpentine interconnect geometry enables remarkable levels of:

- **Stretchability:** Exceeding 300% elongation
- **Reversibility:** Over 200% reversible deformation

These values significantly surpass previous reports, paving the way for highly deformable energy storage solutions Fig. 4. The stretchable battery based on this serpentine ribbon current collector




Figure 4. The fabrication process of PDMS-DIW.

exhibited stable cycling performance when tested under:

1. 100% stretch conditions
2. Periodic stretch conditions

Moreover, the self-similar serpentine ribbon configuration enabled biaxial stretching of the battery, allowing deformation along multiple axes without compromising performance. A notable aspect of these batteries is their exceptional softness and compliance. The effective modulus of the full battery structure is only slightly higher than the silicone substrate, making the batteries remarkably soft and conformable to curved surfaces or dynamic movements [12].

3.1 Self-Similar Serpentine Design

A key innovation enabling the remarkable stretchability and reversibility of flexible electronics is the self-similar serpentine design. This ingenious geometry allows the device to accommodate significant deformations through out-of-plane rotations, minimizing stress on the materials when stretched or bent. The self-similar serpentine interconnect design enables exceptional levels of:

- **Stretchability:** Exceeding 300% elongation.
- **Reversibility:** Over 200% reversible deformation.

These values significantly surpass previous reports, paving the way for highly deformable and resilient electronic systems. A notable aspect of devices incorporating the self-similar serpentine design is their ability to undergo biaxial stretching [13]. This means the device can deform along

multiple axes without compromising performance, a crucial feature for seamless integration with the human body and its complex movements [14].

4. Wearable Energy-Harvesting Accessory

Harnessing energy from the environment and human body offers a promising solution to power wearable devices sustainably. Several innovative approaches have emerged in this domain:

- **Flexible Solar Panels:** Flexible solar panels can be seamlessly integrated into various surfaces, such as clothing or accessories, to capture and store energy from sunlight. This renewable energy source is particularly advantageous for outdoor applications.
- **Biofuel Cells (BFCs):** BFCs can harvest chemical energy from bodily fluids like sweat, blood, and saliva, achieving power densities up to 3.5 mW cm⁻². These devices offer a unique opportunity to power wearable electronics using the human body's natural processes.
- **Piezoelectric and Triboelectric Nanogenerators:** Piezoelectric nanogenerators (PENGs) and triboelectric nanogenerators (TENGs) can convert body movements and vibrations into electrical energy. PENGs have achieved power densities up to 167 W cm⁻², while TENGs have reached power outputs of 816.6 mW m⁻², making them suitable for powering motion-based wearable devices.
- **Radio Frequency (RF) Energy Harvesters:** These devices can convert ambient RF signals, such as those from cellular networks or Wi-Fi, into usable electrical power. Reported efficiencies exceed 70%, with power densities of up to 500 W cm⁻², enabling wireless power transfer for wearable electronics.

Researchers have also explored hybrid approaches that combine multiple energy harvesting technologies into a single system, improving overall efficiency for wearable applications. For instance:

- **Self-Powering "Electronic Skin" (e-skin):** Developed by Caltech, these devices can harvest energy from human sweat and movement to power sensors and data transmission.
- **Kinefox GPS Tracker:** Inspired by self-winding watches, this wildlife tracker developed by researchers from the University of Copenhagen, Technical University of Denmark, and Max Planck Institute can recharge simply through the animal's movement.

While these innovations hold immense potential, key challenges remain, including improving energy density, environmental stability, industrialization, and standardization of flexible energy harvesters Fig. 5.

4.1 Performance and Integration

Ongoing research and development efforts are focused on improving the performance, lowering the costs, and increasing the scalability of flexible electronics. Key areas of focus include:

1. **Material Advancements:** Developing new materials and optimizing existing ones to enhance properties like conductivity, flexibility, and durability. Promising materials under investigation include graphene, carbon nanotubes, and conductive polymers.
2. **Manufacturing Techniques:** Refining fabrication processes like 3D printing, physical transfer, and solution processing to enable mass production of flexible electronics with consistent quality and reduced costs.
3. **Integration with AI and Edge Computing:** Combining flexible electronics with artificial intelligence (AI) and edge computing capabilities can enable real-time data processing and decision-making in wearable devices, enhancing their functionality and responsiveness.




Figure 5. Stretchable ultrasonic device.

Despite the significant progress, several challenges need to be addressed to further the adoption of flexible electronics:

- **Material Durability:** Ensuring the long-term reliability and resilience of flexible materials under various environmental conditions and repeated deformations.
- **Standardization:** Establishing industry standards and guidelines for the design, manufacturing, and testing of flexible electronics to facilitate their widespread adoption.
- **Security and Privacy:** Implementing robust security measures and privacy protocols to protect sensitive data collected and transmitted by flexible electronic devices, especially in wearable and Internet of Things (IoT) applications.

The integration of flexible electronics with various technologies is driving innovation across multiple sectors as given in Table 1:

Table 1. Sector wise applications

Sector	Applications
Consumer Electronics	Bendable and foldable smartphones, tablets, rollable displays
Wearable Technology	Smartwatches, fitness trackers, health monitoring devices
Internet of Things	Flexible sensors for environmental monitoring, smart home automation
Automotive	Flexible displays, sensors, and lighting for improved vehicle design and safety
Healthcare	Wearable health monitors, smart bandages, implantable devices

5. Potential Applications

The potential applications of flexible electronics span a wide range of industries and domains, revolutionizing how we interact with technology and enabling seamless integration with the human body and our surroundings Fig. 6.



Figure 6. Self-powered sweat monitor system.

- **Consumer Electronics:**
 - Bendable and foldable smartphones, tablets, and wearables that can be easily carried and stored
 - Rollable displays that are compact yet provide larger screen sizes
- **Wearable Technology:**
 - Smartwatches, fitness trackers, and health monitoring devices that conform to the body's contours.
 - Textile-based wearables (e-textiles) embedded with sensors to monitor ECG, EEG, EMG, and other vital signs
 - Tattoo-based wearables (e-skins) that provide better skin contact and signal quality for monitoring ECG, EMG, EEG, and blood pressure
- **Healthcare:**
 - Wearable health monitors and smart bandages that are comfortable and less invasive.
 - Implantable devices that can adapt to the body's movements
 - Sweat-based wearables to monitor sweat composition like electrolytes, glucose, and lactate
 - Tear-based wearables for glucose monitoring and diabetes management

- Printed electronics enabling low-cost, flexible glucose test strips for at-home monitoring
- **Internet of Things (IoT):**
 - Flexible sensors and electronics integrated into clothing, packaging, and everyday objects for environmental monitoring, smart home automation, and more
- **Automotive:**
 - Flexible displays, sensors, and lighting to improve vehicle design and safety
- **Environmental Monitoring:**
 - Sensors integrated into clothing or accessories to measure air quality, UV radiation, and other environmental factors
- **Energy Harvesting:**
 - Flexible solar panels and energy-harvesting devices integrated into various surfaces

The market for healthcare products containing flexible electronics is forecasted to exceed \$8.3 billion by 2030, driven by the trend towards decentralized healthcare and remote patient monitoring. Flexible electronics enable the development of electronic skin patches that can be worn during daily routines, with data wirelessly transmitted, as well as smart textiles that monitor vital signs

6. Conclusion

The advent of flexible electronics has ushered in a new era of seamless integration between technology and the human body. By conforming to natural movements and contours, these innovative devices have opened up a world of possibilities in various sectors, from wearable computing and biomedical devices to environmental monitoring and energy harvesting. With ongoing advancements in materials, manufacturing techniques, and integration with emerging technologies like AI and edge computing, flexible electronics are poised to revolutionize how we interact with our surroundings and monitor our well-being. As we navigate the future, the potential applications of flexible electronics continue to expand, promising more comfortable and unobtrusive wearable devices, implantable medical technologies, and seamless integration of electronics into everyday objects. However, challenges remain in terms of material durability, standardization, and addressing security and privacy concerns. By addressing these challenges, the field of flexible electronics will undoubtedly unlock unprecedented opportunities for innovation, reshaping the way we live, work, and experience the world around us.

References

- [1] Musa Mahmood, Deogratias Mzurikwao, Yun-Soung Kim, Yongkuk Lee, Saswat Mishra, Robert Herbert, Audrey Duarte, Chee Siang Ang, and Woon-Hong Yeo. “Fully portable and wireless universal brain–machine interfaces enabled by flexible scalp electronics and deep learning algorithm”. In: *Nature Machine Intelligence* 1.9 (2019), pp. 412–422.
- [2] Sanghoon Lee, Qiongfeng Shi, and Chengkuo Lee. “From flexible electronics technology in the era of IoT and artificial intelligence toward future implanted body sensor networks”. In: *APL Materials* 7.3 (2019).
- [3] Marie Chan, Daniel Estève, Jean-Yves Fourniols, Christophe Escriba, and Eric Campo. “Smart wearable systems: Current status and future challenges”. In: *Artificial intelligence in medicine* 56.3 (2012), pp. 137–156.
- [4] Jamin Casselman, Nicholas Onopa, and Lara Khansa. “Wearable healthcare: Lessons from the past and a peek into the future”. In: *Telematics and Informatics* 34.7 (2017), pp. 1011–1023.
- [5] MESUT Çiçek. “Wearable technologies and its future applications”. In: *International Journal of Electrical, Electronics and Data Communication* 3.4 (2015), pp. 45–50.

- [6] Jaemin Kim, Jongsu Lee, Donghee Son, Moon Kee Choi, and Dae-Hyeong Kim. “Deformable devices with integrated functional nanomaterials for wearable electronics”. In: *Nano Convergence* 3 (2016), pp. 1–13.
- [7] Hao Wu, YongAn Huang, Feng Xu, Yongqing Duan, and Zhouping Yin. “Energy harvesters for wearable and stretchable electronics: from flexibility to stretchability”. In: *Advanced materials* 28.45 (2016), pp. 9881–9919.
- [8] Bahare Mohamadzade, Raheel M Hashmi, Roy BVB Simorangkir, Reza Gharaei, Sabih Ur Rehman, and Qammer H Abbasi. “Recent advances in fabrication methods for flexible antennas in wearable devices: State of the art”. In: *Sensors* 19.10 (2019), p. 2312.
- [9] Vladimir Leonov and Ruud JM Vullers. “Wearable electronics self-powered by using human body heat: The state of the art and the perspective”. In: *Journal of Renewable and Sustainable Energy* 1.6 (2009).
- [10] Ali K Yetisen, Juan Leonardo Martinez-Hurtado, Barış Ünal, Ali Khademhosseini, and Haider Butt. “Wearables in medicine”. In: *Advanced Materials* 30.33 (2018), p. 1706910.
- [11] Hanlu Ye, Meethu Malu, Uran Oh, and Leah Findlater. “Current and future mobile and wearable device use by people with visual impairments”. In: *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*. 2014, pp. 3123–3132.
- [12] Joanna Berzowska. “Electronic textiles: Wearable computers, reactive fashion, and soft computation”. In: *Textile* 3.1 (2005), pp. 58–75.
- [13] Thomas Sanniccolo, Mélanie Lagrange, Anthony Cabos, Caroline Celle, Jean-Pierre Simonato, and Daniel Bellet. “Metallic nanowire-based transparent electrodes for next generation flexible devices: a review”. In: *Small* 12.44 (2016), pp. 6052–6075.
- [14] Suranga Seneviratne, Yining Hu, Tham Nguyen, Guohao Lan, Sara Khalifa, Kanchana Thilakarathna, Mahbub Hassan, and Aruna Seneviratne. “A survey of wearable devices and challenges”. In: *IEEE Communications Surveys & Tutorials* 19.4 (2017), pp. 2573–2620.